


Grinders for Depressed Center Wheels, Cut Off Wheels & Flap Wheels

3" (75 mm) – 6" (150 mm)
.9 H.P. (675 W)



Air Inlet Size: 1/4" NPT
Hose Size Recommendations: 3/8" (10 mm)

Extra Charge Accessories

- Type 27 Adapters
- Sanding Pads

Standard Equipment

- Tool • Operating Instructions and Service Manual
- 2 Wrenches (sizes based on options)

The depressed center wheel adapters are not supplied as standard equipment with the tools. If you are using a wheel that requires the adapters, they must be purchased separately.

Model Number	Spindle Thread	Guard Size	Rated Speed	Throttle Type	
				Standard Lever	Safety Lever
44RA	3/8-24	4 Inch (100mm)	11000 R.P.M.	44RA4;427	44RA4K;427
	5/8-11	4 1/2 (115mm)		44RA2;4527	44RA2K;4527
44RAE	3/8-24	4 Inch (100mm)	11000 R.P.M.	44RAE4;427	44RAE4K;427
	5/8-11	4 1/2 (115mm)		44RAE2;4527	44RAE2K;4527
	3/8-24	6 Inch (150mm)	10000 R.P.M.	44RAE4;641	44RAE4K;641
	5/8-11		44RAE2;641	44RAE2K;641	
46RA	3/8-24	4 Inch (100mm)	15000 R.P.M.	46RA1;427	46RA1K;427
48RA	3/8-24	4 Inch (100mm)	11000 R.P.M.	48RA4;427	48RA4K;427
	5/8-11	4 1/2 (115mm)		48RA2;4527	48RA2K;4527
	3/8-24	6 Inch (150mm)	10000 R.P.M.	48RA4;641	48RA4K;641
	5/8-11		48RA2;641	48RA2K;641	

