# TOP CATO8 CLASSIC LINE

**Insert Style Collets** 

0.9 H.P. (675 W)

### **Insert Style Die Grinders For Carbide Burrs & Mounted Stones**

40GK 4121G

Quick Order Number Die Grinders

#### Air Inlet Size: 1/4" NPT

Hose Size Recommendations: 3/8" (10 mm)

**Extra Charge Accessories** 

## Safety Lever Standard Equipment


- Tool Operating Instructions and Service Manual
- 2 Wrenches (sizes based on options)
- 0.9 H.P. **Throttle Type** Model Number (675 W) **Collet Size Rated Speed Standard Lever Safety Lever** 18000 R.P.M. 40G;18 40GK;18 40G 30 cfm (14.2 L/s) Max 22000 R.P.M. 40G:22 40GK:22 1/4 Inch 18000 R.P.M. 4121G;18 4121GK;18 4121G 22000 R.P.M. 4121G;22 4121GK;22 40GK 4121GK 5.80 Inch 6.36 Inch (147.3 mm) (161.6 mm) bs b 1.5 Lb. (0.7 Kg) 1.5 Lb. (0.7 Kg) 1.62 Inch 1.62 Inch

## **T<sup>®</sup>P CAT08 CLASSIC LINE**

40GHK

### **Grinders For Type 1 Wheels, Flap Wheels And Wire Wheels**

(41.1 mm)



Circular Wire Wheels Circular Flap Wheels S



0

## Type 1 Wheel

Air Inlet Size: 1/4" NPT

#### Hose Size Recommendations: 3/8" (9.5 mm)

(41.1 mm)


#### **Extra Charge Accessories**

- Cone Wheel Adapters Heavy-Duty 2-pc. Collets
- Erickson Style Collets Safety Lever Extended Length Spindle
- +2 and +3 spindles for use with buffing wheels (40GH & 47GH only)

#### **Standard Equipment**

- Tool Operating Instructions and Service Manual
- 2 Wrenches (sizes based on options)

Quick Order Number Horizontal T1 Wheel Grinders				
Model Number	Guard Size	Rated Speed	Throttle Type	
			Standard Lever	Safety Lever
40GH	3 Inch (75mm)	18000 R.P.M.	40GH;301	40GHK;301
	4 Inch (100mm)	15000 R.P.M.	40GH;401	40GHK;401



40GH Series

3" (75 mm) – 4" (100 mm) 0.9 H.P. (675 W)